



MoFlow Air Filter Assembly Instructions 2008-2009 FLH only

WARNING! This product is intended to be used on racing vehicles, on closed courses, and not for use on roads or vehicles otherwise subject to emissions control requirements. In California, this product should not be used on any vehicle that is registered or licensed for use on public streets.

1. Remove the stock air cleaner and crankcase breather hardware. Refer to the manufacturer service manual.
2. Remove the black metal plate that connects the throttle body to the heads and discard
3. Clean the carburetor inlet face and both the crankcase breather o-ring surfaces. Remove all dust and/or grease.
4. Install gasket supplied with the new kit. Be careful to line up all the holes.
5. Locate the new base assembly. Be sure the four o-rings are installed in the grooves.
Tip: If the o-rings do not stay in the grooves a small amount of grease can be applied to the o-ring to keep it in place for installation.
6. Install the base assembly with two banjo bolts and six flat washers (stack two washers between the breather block and the head and one between the breather bolt head and the breather block, but do not tighten the banjo bolts fully at this time. Just Look at the instructions.
7. Install three button head bolts through the base into the carburetor/ throttle body.
Note: Fuel injection applications may require loosening the intake manifold for proper alignment. (Be sure to retighten after alignment.)
8. Torque the button head bolts to **3-5 ft-lbs** (36-60 in-lbs) and the banjo bolts to **10-12 ft-lbs** (120-144 in-lbs).
9. Install the aluminum velocity stack onto the base. *Note: The velocity stack is a slip fit.*
10. Then install the silve ring on top of the velocity stack.
11. Install the Air Aide air filter element. *Note: The chrome cover holds the filter, the velocity stack and the silver safety ring in place.*
12. Install the billet cover with three hex head bolts.
Tip: Do not force the cover in place. Check the Filter and Velocity Stack for proper location.
13. Torque the hex head bolts to **3-5 ft-lbs** (36-60 in-lbs).

Tip: Use of "Loctite" is required with this kit. Two drops should be applied to every bolt just before the bolt is to be installed!!

DO NOT INSTALL THIS UNIT WITHOUT APPLYING LOCKTITE TO EVERY SCREW, NUT OR BOLT!!

- Note:**
- After this installation it is recommended that the engine air fuel ratio be checked.
 - Carburetor should be checked accordingly within California (CARB) guidelines.
 - Fuel injected models are to be remapped accordingly within California (CARB) guidelines using an approved remapping device such as a Zippers T-MAX 50
 - Check the banjo bolts for proper torque every 2500 miles.

OUR WARRANTY POLICY

Cycle Visions' obligation under "Our Warranty Policy" is limited to one (1) year from date of purchase to repair or replacement of the defective item (s). Chrome, polished, powder-coated, anodized finishes, or electrical parts are limited to thirty (30) day from date of purchase.

This warranty will be void on all products that show evidence of misapplication, improper installation, abuse, lack of proper maintenance, negligence, or alteration from their original design.

The consumer will be responsible for removing from the vehicle any defective item (s), transportation costs prepaid and for reinstallation upon return by Cycle Visions. The loss of use of the product, loss of time, inconvenience, commercial loss or consequential damages is not covered. Cycle Visions reserves the right to change the design of any product without assuming any obligation to modify any product previously manufactured. Warranty returns of Cycle Visions products are few because of our high quality products.

Carefully inspect all parts... If you find that your parts arrived in damaged conditional all original packaging material (box and other materials) must be saved to make a proper damage claim within seven (7) days. You must be able to present the damaged boxes and materials to the freight carrier to verify your claim. The user shall assume all legal, personal, injury risk and liability and all other obligations, duties and risks associated therewith.

www.cyclevisions.com

Cycle Visions™

San Diego, California (619) 295.7800

Rev. 06/09

See our other products on the web! Made in the USA